

Solarleuchten | Serie:
Home 401, Home 402, Home 403

Schutzart: **IP 54**
Schutzklasse: III

Gehäuse Aluminium-Druckguss pulverbeschichtet. Mit PIR-Sensor und 2 W Solarmodul für LED mit Lithium-Akku 3,7V/2,2Ah (5 W Solarmodul | Akku 4,4Ah Home 403) und Kunststoff-Erdspieß. Aufladezeit: 6-8 Stunden bei Tageslicht Betriebsdauer: 2,5-3 Stunden (Vollast), 20-25 Stunden (bei Dämmerungslicht) bzw. 12-15 Stunden (mit wechselnder Lichtleistung). Mit Lichtaustrittfenster PC klar.

Leuchtmittel (LED) im Lieferumfang enthalten.
Lieferbare Farbe: anthrazit metallic

Bestellnummer | Abmessungen | Lampe |
Reference number | Dimensions | Lamp

Solar luminaires | Series:
Home 401, Home 402, Home 403

Type of Protection: **IP 54**
Protection Class: III


Housing pressure die-cast aluminium, powder-coated. Including PIR sensor, 2W solar module for LED with lithium battery 3.7V/2.2Ah (5W solar modul | battery 4.4Ah Home 403) and plastic ground spike. Charging time: 6-8 hours in daylight

Operating time: 2,5-3 hours (continuous operation), 20-25 hours (in twilight), 12-15 hours (with different light output levels). With light-emission window PC clear. LED included.

Available colour: anthracite metallic

Lichtfarbe | Leuchtenlichtstrom | Dimmbarkeit | Serie | € brutto
Light colour | Luminaire flux | Dimmable | Series | o. MwSt. |
€ gross without VAT

Solarleuchten Solar luminaires			Preisgruppe 12 Price Category 12			
612154.0031.19	L 140, B 140, H 340	LED	830	50 lm	on/off Home 401	144,50
612155.0031.19	L 140, B 140, H 400	LED	830	120 lm	on/off Home 402	149,70
612156.0031.19	L 200, B 200, H 245	LED	830	250 lm	on/off Home 403	169,80



- Geeignet für Fest- und Erdspießmontage
- Schrauben aus Edelstahl
- Blendfreies Licht
- Homogene Lichtverteilung

- Suitable for fixed mounting or ground-spike mounting
- Stainless steel screws
- Glarefree light
- Homogeneous light distribution



© Fotostudio Lippmann